

ONLEVEL

**ONLY
YOU**

ANY COLOUR, ANY SIZE
WITHIN 15 DAYS

AIRFORCE

AIRFORCE

CANTILEVER GLASS CANOPY

NEW: ONLINE CONFIGURATOR

AIRFORCE

The only glass canopy you need to know.

AIRFORCE on Roofing Surveillance Mission

Our reconnaissance task: As we know that we can't count on dream weather every day, our Innovation Hotbed came up with a height-adjustable canopy with an integrated, self-triggering cover. As a matter of fact, the ONLEVEL Product Pioneers also had a user-friendly installation in mind for you to whip up your project quickly and stressfree.


Winner, say hello to the sun!

ONLEVEL Airforce goes off like a rocket – when it comes to product innovations, it's already now our winner of the year.

AIRFORCE never leaves you out in the cold and makes you fly high. For your fast propulsion, the ONLEVEL Product Pilots, as always, made sure installation is as easy as can be: Airforce is height adjustable and other lengths or colours on request.


Essential Features

- | Securing the glass from the side
- | Height adjustable with integrated, self-triggering cover
- | Simple mounting
- | Concealed fastening
- | One-sided fastening, no drawbars required
- | Several profiles can be connected to each other
- | Slight glass processing for securing glass panes
- | Only the lower pane requires glass processing, therefore no drilling offset for laminated safety glass
- | Suitable for 17.52 and 21.52 mm glass
- | 10° inclination
- | **AbZ** tested



Glass	max. glass projection	min. width	max. width
17.52 mm VSG glass made of TVG with SGP film	1000 mm	1390 mm	3000 mm
21.52 mm VSG glass made of TVG with PVB film	1100 mm	1390 mm	3000 mm
21.52 mm VSG glass made of TVG with SGP film	1100 mm	1390 mm	3000 mm
21.52 mm VSG glass made of TVG with SGP film	1200 mm	1590 mm	3000 mm

Height adjustable with integrated,
self-triggering cover



Suitable for 17.52 and 21.52 mm glass

AIRFORCE | SYSTEM

AIRFORCE







The AIRFORCE system includes:

- Glass Profile
- Cover Cap Profile
- Glass Rubber
- Plastic Profile Backside
- Plastic Profile Frontside
- Fixation Blocks
- Self-closing Cover Strip for clipping
- Endcaps


- | Completely pre-assembled
- | For 17.52 mm (8/8/4) and 21.52 mm (10/10/4) laminated safety glass made of thermally toughened glass with PVB or SGP film
- | Sales unit: 1 piece

Length	1400 mm	1600 mm	2000 mm	2400 mm	2800 mm	3200 mm	3500 mm	4000 mm	4500 mm	5000 mm
Surface	Art. no.									
mill finish	17.1014.020.10	17.1016.020.10	17.1020.020.10	17.1024.020.10	17.1028.020.10	17.1032.020.10	17.1035.020.10	17.1040.020.10	17.1045.020.10	17.1050.020.10
plain anodised	17.1014.020.11	17.1016.020.11	17.1020.020.11	17.1024.020.11	17.1028.020.11	17.1032.020.11	17.1035.020.11	17.1040.020.11	17.1045.020.11	17.1050.020.11
RAL glossy	17.1014.020.13	17.1016.020.13	17.1020.020.13	17.1024.020.13	17.1028.020.13	17.1032.020.13	17.1035.020.13	17.1040.020.13	17.1045.020.13	17.1050.020.13
RAL structured	17.1014.020.16	17.1016.020.16	17.1020.020.16	17.1024.020.16	17.1028.020.16	17.1032.020.16	17.1035.020.16	17.1040.020.16	17.1045.020.16	17.1050.020.16
RAL matt	17.1014.020.18	17.1016.020.18	17.1020.020.18	17.1024.020.18	17.1028.020.18	17.1032.020.18	17.1035.020.18	17.1040.020.18	17.1045.020.18	17.1050.020.18
ARMOR RAL	17.1014.020.19	17.1016.020.19	17.1020.020.19	17.1024.020.19	17.1028.020.19	17.1032.020.19	17.1035.020.19	17.1040.020.19	17.1045.020.19	17.1050.020.19

Glass cut-out



- | 17.52mm VSG glass made of TVG with SGP film, max. glass projection 1000mm, min width 1390 mm
- | 21.52mm VSG glass made of TVG with PVB or SGP film, max. glass projection 1100mm, min width 1390 mm
- | 21.52mm VSG glass made of TVG with SGP film, max. glass projection 1200mm, min width 1590 mm
- | Max. glass width 3000mm
- | Glass width (L) 10mm less than profile width




Glass thickness (G)

8/8/4 (17.52 mm)

10/10/4 (21.52 mm)



Glass canopy



Sum *

€ 580.00

Gross prices (excl. glass panels, wall screws and VAT)

1. Dimensions

1.1 Quantity

1 pcs

1.2 Length

(1400mm - 12000mm)

1400 mm

1390



AUTOMATIC DETERMINATION OF GLASS DIMENSIONS



3D VIEW OF THE PLANNED CONFIGURATION



DOWNLOAD FUNCTION WITH ALL DIMENSIONS AND THE REQUIRED GLASS PROCESSING


CONFIGURE IT OUT!

THE AIRFORCE CONFIGURATOR FROM ONLEVEL.


WWW.ONLEVEL-SHOP.COM

AIRFORCE | MOUNTING ON CONCRETE

Connection to concrete



Connection to concrete with isolation




AIRFORCE | MOUNTING ON CONCRETE

Fischer fixing anchor FAZ II 12/20



| Finish exterior application: V4A (exterior)
 | Required number per 2500 mm: 7 pieces
 | M12
 | Sales unit: 20 pieces




Model 3501	AISI 316 (exterior)
Art. no.	
91.3501.220.30	

Mounting set on concrete with insulation M12x400mm



| Sales unit: 8 pieces




Model 9005	AISI 316 (exterior)	AISI 304
Art. no.		Art. no.
17.9005.012.30		17.9005.012.20

Pressure-resistant insulation



| Length 600 or 1200 mm
 | Sales unit: 1 piece




Model 9006	600 mm	1200mm
Thickness (t)	Art. no.	Art. no.
10mm	17.9006.016.00	17.9006.010.00
100 mm	17.9006.106.00	17.9006.100.00
150 mm	17.9006.156.00	17.9006.150.00
200 mm	17.9006.206.00	17.9006.200.00

Fischer fixing anchor SXRL




| AISI 316 (exterior)
 | Sales unit: 2 pieces



Ø	Length	Art. no.
8mm	160mm	91.3580.816.30
10mm	200mm	91.3581.020.30
10mm	230mm	91.3581.023.30
10mm	260mm	91.3581.026.30
10mm	290mm	91.3581.029.30


AIRFORCE | MOUNTING ON WOOD

Connection to wood for 8/8/4 (17.52) glass



Mounting set on wood M12x200mm


| Sales unit: 8 Stück



Model 9004	AISI 316 (exterior)	AISI 304
	Art. no.	Art. no.
	17.9004.012.30	17.9004.012.20


AIRFORCE | MOUNTING ON WOOD

Connection to wood for 10/10/4 (21.52) glass




AIRFORCE | MOUNTING ON STEEL

Connection to steel



Mounting set on steel M12x50mm

| one anchor is required per 400mm
| Sales unit: 4 pieces



Model 9003	AISI 316 (exterior)	AISI 304
	Art. no.	Art. no.
	17.9003.012.30	17.9003.012.20



HEIGHT ADJUSTABLE MOUNTING BLOCK.

The Steady and Flexible Body.

We wouldn't be ONLEVEL, if we didn't work permanently for the further development of our products: We have enabled a more significant compensation of construction and mounting tolerances by taking optimum advantage of the opportunities provided by aluminium extrusions.

Therefore, the drill hole for fixing our glass support profiles does not need to be completely accurate any more, but has a tolerance of approx. 5 mm in each direction. In order to guarantee that the glass balustrade remains in place, the mounting block is equipped with teeth. In this way, a force-locked connection is achieved. Therefore always pay attention to the logo indicating the suitable application types.

Mounting block is included in the AIRFORCE set



AIRFORCE | ACCESSOIRES

Mortar FIS SB 390 S



| For chemical anchor bonding
| Including 2 mixers
| Sales unit: 1 piece

Model 3000	
	Art. no.
	91.3000.010.00

Dispensing device



| For use with mortar (91.3000.010.00)
| Sales unit: 1 piece

Model 3002	Plastic
	Art. no.
Gun	91.3002.010.00
Mixer	91.3002.011.00

Airpump



| For blowing out the drill holes
| Sales unit: 1 piece

Model 3001	Plastic
	Art. no.
	91.3001.010.00

Anchor hole brush



| For cleaning the drill holes
| Ø 12 mm
| Sales unit: 1 piece


Model 3002	Plastic
	Art. no.
	91.3002.012.00

Extension pin



- | Infinite extensions?
No problem, we remove the end cap for you
- | Length: 40 mm
- | Diameter Ø 6 mm
- | Sales unit: 8 pieces

Model 7001	V4A (interior & exterior)
Art. no.	
90.7001.640.31	




Screw for mounting the end cap



- | Countersunk head screw with Torx ISO 14587 Ø3.9x16mm, V2A
- | is required if the length of the profile is shortened

Modell 1240	V2A (Exterior)
Art. no.	
91.1240.416.20	

Cutting Airforce



Art. no.	
95.0000.019.02	

AIRFORCE | OUTDOOR USE







ONLEVEL

ONLEVEL Ltd. | Unit 7, Alexandria Court | Alexandria Drive

Ashton Commerce Park | Ashton-under-Lyne | Lancashire OL7 0QN | United Kingdom
T +44 0161 804 9500 | F +44 0161 804 9505 | info@onlevel-uk.com | www.onlevel.com